

## Water supply/electricity/general application

OD PN	SDR26 6.3	SDR21 8	SDR17 10	SDR13.6 12.5	SDR11 16	SDR9 20	SDR7.4 25
12							1.8 +0.4 - 0
16 +0.3 - 0						1.8 +0.4 - 0	2.2 +0.5 - 0
20 +0.3 - 0				1.8 +0.4 - 0	1.9 +0.4 - 0	2.3 +0.5 - 0	2.8 +0.5 - 0
25 +0.3 - 0			1.8 +0.4 - 0	1.9 +0.4 - 0	2.3 +0.5 - 0	2.8 +0.5 - 0	3.5 +0.6 - 0
32 +0.3 - 0			1.9 +0.4 - 0	2.4 +0.5 - 0	2.9 +0.5 - 0	3.6 +0.6 - 0	4.4 +07 - 0
40 +0.4 - 0	1.8 +0.4 - 0	1.9 +0.4 - 0	2.4 +0.5 - 0	3.0 +0.5 - 0	3.7 +0.6 - 0	4.5 +0.7 - 0	5.5 +0.8 - 0
50 +0.5 - 0	2.0 +0.4 - 0	2.4 +0.5 - 0	3.0 +0.5 - 0	3.7 +0.6 - 0	4.6 +0.7 - 0	5.6 +0.8 - 0	6.9 +0.9 - 0
63 +0.6 - 0	2.5 +0.5 - 0	3.0 +0.5 - 0	3.8 +0.6 - 0	4.7 +0.7 - 0	5.8 +0.8 - 0	7.1 +1.0 - 0	8.6 +1.1 - 0
75 +0.7 - 0	2.9 +0.5 - 0	3.6 +0.6 - 0	4.5 +0.7 - 0	5.6 +0.8 - 0	6.8 +0.9 0	8.4 +1.1 - 0	10.3 +1.3 - 0
90 +0.9 - 0	3.5 +0.6 - 0	4.3 +0.7 - 0	5.4 +0.8 - 0	6.7 +0.9 - 0	8.2 +1.1 - 0	10.1 +1.3 - 0	12.3 +1.5 - 0
110 +1.0 - 0	4.2 +0.7 - 0	5.3 +0.8 - 0	6.6 +0.9 - 0	8.1 +1.1 - 0	10.0 +1.2 - 0	12.3 +1.5 - 0	15.1 +1.8 - 0
125 +1.2 - 0	4.8 +0.7 - 0	6.0 +0.8 - 0	7.4 +1.0 - 0	9.2 +1.2 - 0	11.4 +1.4 - 0	14.0 +1.6 - 0	17.1 +2.0 - 0
140 +1.3 - 0	5.4 +0.8 - 0	6.7 +0.9 - 0	8.3 +1.1 - 0	10.3 +1.3 - 0	12.7 +1.5 - 0	15.7 +1.8 - 0	19.2 +2.2 - 0
160 +1.5 - 0	6.2 +0.9 - 0	7.7 +1.0 - 0	9.5 +1.2 - 0	11.8 +1.4 - 0	14.6 +1.7 - 0	17.9 +2.0 - 0	21.9 +2.4 - 0
180 +1.7 - 0	6.9 +0.9 - 0	8.6 +1.1 - 0	10.7 +1.3 - 0	+1.6 13.3 - 0	16.4 +1.9 - 0	20.1 +2.3 - 0	24.6 +2.7 - 0
200 +1.8	7.7 +1.0	9.6 +1.2	11.9 +1.4	+1.7	18.2 +2.1	22.4 +2.5	27.4 +3.0

- 0	- 0	- 0	- 0	14.7	- 0	- 0	- 0	- 0							
225	+2.1	8.6	+1.1	10.8	+1.3	13.4	+1.6	16.6	+1.9	20.5	+2.3	25.2	+2.8	30.8	+3.3
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
250	+2.3	9.6	+1.2	11.9	+1.4	14.8	+1.7	18.4	+2.1	22.7	+2.5	27.9	+3.0	34.2	+3.7
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
280	+2.6	10.7	+1.3	13.4	+1.6	16.6	+1.9	20.6	+2.3	25.4	+2.8	31.3	+3.4	38.3	+4.1
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
315	+2.9	12.1	+1.5	15.0	+1.7	18.7	+2.1	23.2	+2.6	28.6	+3.1	35.2	+3.8	43.1	+4.6
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
355	+3.2	13.6	+1.6	16.9	+1.9	21.1	+2.4	26.1	+2.9	32.2	+3.5	39.7	+4.2	48.5	+5.1
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
400	+3.6	15.3	+1.8	19.1	+2.2	23.7	+2.6	29.4	+3.2	36.3	+3.9	44.7	+4.7	54.7	+5.7
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
450	+3.8	17.2	+2.0	21.5	+2.4	26.7	+2.9	33.1	+3.6	40.9	+4.3	50.3	+5.3	61.5	+6.4
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
500	+4.0	19.1	+2.2	23.9	+2.6	29.7	+3.2	36.8	+3.9	45.4	+4.8	55.8	+5.8	68.3	+7.1
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		- 0
560	+4.3	21.4	+2.4	26.7	+2.9	33.2	+3.6	41.2	+4.4	50.8	+5.3	62.5	+6.5		
	- 0		- 0		- 0		- 0		- 0		- 0		- 0		
630	+4.6	24.1	+2.7	30.0	+3.2	37.4	+4.0	46.3	+4.9	57.2	+6.0				
	- 0		- 0		- 0		- 0		- 0		- 0				
710	+6.4	27.2	+5.4	33.9	+6.7	42.1	+8.4	52.2	+10.4	64.5					
	- 0		- 0		- 0		- 0		- 0						
ISO4427 Specification															
PE100															