

給水/電力/一般用管

OD PN	SDR26 6.3	SDR21 8	SDR17 10	SDR13.6 12.5	SDR11 16	SDR9 20	SDR7.4 25
平均外徑 (mm)	壁厚(mm)	壁厚(mm)	壁厚(mm)	壁厚(mm)	壁厚(mm)	壁厚(mm)	壁厚(mm)
12							1.8 +0.4 - 0
16 +0.3 - 0						1.8 +0.4 - 0	2.2 +0.5 - 0
20 +0.3 - 0				1.8 +0.4 - 0	1.9 +0.4 - 0	2.3 +0.5 - 0	2.8 +0.5 - 0
25 +0.3 - 0			1.8 +0.4 - 0	1.9 +0.4 - 0	2.3 +0.5 - 0	2.8 +0.5 - 0	3.5 +0.6 - 0
32 +0.3 - 0			1.9 +0.4 - 0	2.4 +0.5 - 0	2.9 +0.5 - 0	3.6 +0.6 - 0	4.4 +0.7 - 0
40 +0.4 - 0	1.8 +0.4 - 0	1.9 +0.4 - 0	2.4 +0.5 - 0	3.0 +0.5 - 0	3.7 +0.6 - 0	4.5 +0.7 - 0	5.5 +0.8 - 0
50 +0.5 - 0	2.0 +0.4 - 0	2.4 +0.5 - 0	3.0 +0.5 - 0	3.7 +0.6 - 0	4.6 +0.7 - 0	5.6 +0.8 - 0	6.9 +0.9 - 0
63 +0.6 - 0	2.5 +0.5 - 0	3.0 +0.5 - 0	3.8 +0.6 - 0	4.7 +0.7 - 0	5.8 +0.8 - 0	7.1 +1.0 - 0	8.6 +1.1 - 0
75 +0.7 - 0	2.9 +0.5 - 0	3.6 +0.6 - 0	4.5 +0.7 - 0	5.6 +0.8 - 0	6.8 +0.9 0	8.4 +1.1 - 0	10.3 +1.3 - 0
90 +0.9 - 0	3.5 +0.6 - 0	4.3 +0.7 - 0	5.4 +0.8 - 0	6.7 +0.9 - 0	8.2 +1.1 - 0	10.1 +1.3 - 0	12.3 +1.5 - 0
110 +1.0 - 0	4.2 +0.7 - 0	5.3 +0.8 - 0	6.6 +0.9 - 0	8.1 +1.1 - 0	10.0 +1.2 - 0	12.3 +1.5 - 0	15.1 +1.8 - 0
125 +1.2 - 0	4.8 +0.7 - 0	6.0 +0.8 - 0	7.4 +1.0 - 0	9.2 +1.2 - 0	11.4 +1.4 - 0	14.0 +1.6 - 0	17.1 +2.0 - 0
140 +1.3 - 0	5.4 +0.8 - 0	6.7 +0.9 - 0	8.3 +1.1 - 0	10.3 +1.3 - 0	12.7 +1.5 - 0	15.7 +1.8 - 0	19.2 +2.2 - 0
160 +1.5 - 0	6.2 +0.9 - 0	7.7 +1.0 - 0	9.5 +1.2 - 0	11.8 +1.4 - 0	14.6 +1.7 - 0	17.9 +2.0 - 0	21.9 +2.4 - 0

180	+1.7 -0	6.9	+0.9 -0	8.6	+1.1 -0	10.7	+1.3 -0	+1.6 13.3 -0	16.4	+1.9 -0	20.1	+2.3 -0	24.6	+2.7 -0	
200	+1.8 -0	7.7	+1.0 -0	9.6	+1.2 -0	11.9	+1.4 -0	+1.7 14.7 -0	18.2	+2.1 -0	22.4	+2.5 -0	27.4	+3.0 -0	
225	+2.1 -0	8.6	+1.1 -0	10.8	+1.3 -0	13.4	+1.6 -0	16.6	+1.9 -0	20.5	+2.3 -0	25.2	+2.8 -0	30.8	+3.3 -0
250	+2.3 -0	9.6	+1.2 -0	11.9	+1.4 -0	14.8	+1.7 -0	18.4	+2.1 -0	22.7	+2.5 -0	27.9	+3.0 -0	34.2	+3.7 -0
280	+2.6 -0	10.7	+1.3 -0	13.4	+1.6 -0	16.6	+1.9 -0	20.6	+2.3 -0	25.4	+2.8 -0	31.3	+3.4 -0	38.3	+4.1 -0
315	+2.9 -0	12.1	+1.5 -0	15.0	+1.7 -0	18.7	+2.1 -0	23.2	+2.6 -0	28.6	+3.1 -0	35.2	+3.8 -0	43.1	+4.6 -0
355	+3.2 -0	13.6	+1.6 -0	16.9	+1.9 -0	21.1	+2.4 -0	26.1	+2.9 -0	32.2	+3.5 -0	39.7	+4.2 -0	48.5	+5.1 -0
400	+3.6 -0	15.3	+1.8 -0	19.1	+2.2 -0	23.7	+2.6 -0	29.4	+3.2 -0	36.3	+3.9 -0	44.7	+4.7 -0	54.7	+5.7 -0
450	+3.8 -0	17.2	+2.0 -0	21.5	+2.4 -0	26.7	+2.9 -0	33.1	+3.6 -0	40.9	+4.3 -0	50.3	+5.3 -0	61.5	+6.4 -0
500	+4.0 -0	19.1	+2.2 -0	23.9	+2.6 -0	29.7	+3.2 -0	36.8	+3.9 -0	45.4	+4.8 -0	55.8	+5.8 -0	68.3	+7.1 -0
560	+4.3 -0	21.4	+2.4 -0	26.7	+2.9 -0	33.2	+3.6 -0	41.2	+4.4 -0	50.8	+5.3 -0	62.5	+6.5 -0		
630	+4.6 -0	24.1	+2.7 -0	30.0	+3.2 -0	37.4	+4.0 -0	46.3	+4.9 -0	57.2	+6.0 -0				
710	+6.4 -0	27.2	+5.4 -0	33.9	+6.7 -0	42.1	+8.4 -0	52.2	+10.4 -0	64.5					
ISO4427 規格 /PE100															