

## 壓力用管 ( 等級 12.5~16kgf/cm<sup>2</sup> · 安全係數 2.5 )

標稱尺寸		外徑	厚度	工作 壓力	標準 長度	單位 重量	施工法				
mm	吋	mm	mm	kgf/cm <sup>2</sup>	M	kg/M	鎖	套	熔	插	槽
16	1/2	21.5±0.20	2.5±0.20	16	5/100	0.143	√	√			
20	3/4	27.0±0.25	3.0±0.25	16	5/100	0.216	√	√			
25	1	34.0±0.35	3.5±0.30	16	5/100	0.320	√	√			
30	1 1/4	42.0±0.40	4.0±0.30	16	5/50	0.456	√	√			
40	1 1/2	48.0±0.50	4.5±0.35	16	5/50	0.587	√	√			
50	2	60.0±0.60	5.0±0.35	16	5/50	0.899	√	√			
65	2 1/2	76.0±1.10	6.6±0.45	16	5	1.374	√		√		
75	3	89.0±1.30	8.1±0.55	16	5	1.966	√		√		
75	3	89.0±1.30	6.5±0.44	12.5	5	1.75	√		√		
100	4	114.0±1.45	10.4±0.65	16	5	3.232	√		√		
125	5	140.0±1.80	12.7±0.75	16	5	4.850			√		
150	6	165.0±2.00	15.3±0.85	16	5	6.871			√		
200	8	216.0±2.30	19.5±1.10	16	5	11.496			√		
250	10	267.0±2.70	24.3±1.25	16	5	17.694			√		
300	12	318.0±3.20	28.9±1.65	16	5	25.066			√		
350	14	370.0±3.30	33.6±1.80	16	5	33.911			√		
400	16	420.0±3.70	38.2±2.95	16	5	43.757			√		
450	18	457.2±4.10	41.6±3.20	16	5	51.870			√		
500	20	508.0±4.50	46.2±3.55	16	5	64.010			√		
550	22	558.8±5.00	50.8±3.90	16	5	77.424			√		
600	24	609.6±5.40	55.4±4.25	16	5	92.144			√		

\*JIS 規格、CNS2456、CNS2458、PE100

應用範圍：電力、給水、空調、灌溉、化學管線、埋設管線等